

**ROUND HOLE 60° STAGGERED PERFORATED SHEET
PATTERN LIST**

Pattern #	Hole Dia. MM	Centers MM	Opening	SHEET THICKNESS													Material		
				0.5 mm	0.6 mm	0.8 mm	0.9 mm	1.0 mm	1.2 mm	1.4 mm	1.5 mm	2.0 mm	2.5 mm	3.0 mm	4.0 mm	5.0 mm	MS	AL	SS
R0.5T1.5	0.5	1.5	10.08%	✓													✓		✓
R0.6T1.5	0.6	1.5	14.51%	✓															✓
R0.7T1.7	0.7	1.7	15.38%		✓														✓
R0.8T1.6	0.8	1.6	22.67%	✓															✓
R0.8T2.0	0.8	2	14.51%			✓												✓	✓
R1.0T2.0	1	2	22.67%	✓	✓	✓	✓	✓	✓								✓		✓
R1.25T2.5	1.25	2.5	22.67%	✓	✓	✓	✓	✓	✓								✓		✓
R2.0T3.0	2	3	40.31%	✓	✓	✓	✓	✓	✓								✓	✓	✓
R2.0T4.0	2	4	22.67%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓				✓	✓	✓
R2.5T5.0	2.5	5	22.67%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓
R3.0T4.0	3	4	51.01%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓
R3.0T5.0	3	5	32.65%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓					
R3.0T6.0	3	6	22.67%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R4.0T6.0	4	6	40.31%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R4.0T7.0	4	7	29.61%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R4.0T8.0	4	8	22.67%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R5.0T7.0	5	7	46.27%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R5.0T8.0	5	8	35.43%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R5.0T9.0	5	9	27.99%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R5.0T10	5	10	22.67%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R6.0T8.0	6	8	51.01%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R6.0T8.5	6	8.5	45.19%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R6.0T9.0	6	9	40.31%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R6.0T10	6	10	32.65%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R6.0T12	6	12	22.67%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R8.0T10	8	10	58.04%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R8.0T11	8	11	47.97%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R8.0T12	8	12	40.31%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R8.0T13	8	13	34.34%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R8.0T14	8	14	29.61%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R8.0T15	8	15	25.80%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓



R8.0T16	8	16	22.67%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R9.0T12	9	12	51.01%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R9.0T13	9	13	43.47%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R9.0T14	9	14	37.48%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R9.0T15	9	15	32.65%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R9.0T16	9	16	28.69%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R9.0T17	9	17	25.42%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R9.0T18	9	18	22.67%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R10T13	10	13	53.66%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R10T14	10	14	46.27%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R10T15	10	15	40.31%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R10T16	10	16	35.43%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R10T17	10	17	31.38%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R10T18	10	18	27.99%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R10T19	10	19	25.12%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R10T20	10	20	22.67%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R15T20	15	20	51.01%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R15T25	15	25	32.65%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R15T30	15	30	22.67%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R20T25	20	25	58.04%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R20T30	20	30	40.31%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R20T40	20	40	22.67%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R25T35	25	35	46.27%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R25T40	25	40	35.43%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R25T50	25	50	22.67%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R30T50	30	50	32.65%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
R30T50	30	60	22.67%	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓